

# A2024TI-20

## CARS, LIGHT TRUCK TIRE CHANGERS

The market choice for reliability and long-lasting performance is designed for low-profile/ultra-high performance tires. Run-flat certified by all major tire manufacturers. PAX capable with accessory kit.

# 24"



Same features as the A2024TI

## PLUS SP2000

### SUPER POWER UNIT

- Pneumatic-powered upper disc holds bead into the wheel drop for mounting
- Designed for low-profile, EMT and high-performance tires and wheels
- Loosening upper bead for demounting
- Push down upper bead for lubrication and tire tool insertion
- Lowering upper bead for inspection between bead and demount head
- Lowering upper bead for inserting the bead clamp; this clamp makes it possible to lift the bead over the mount/demount head
- Shipping weight 815 lbs.



seguì Corgi - follow Corgi

# A2024TI



## FEATURES

- Built-in table inflator with jets in the jaws.
- Unique mount/demount head does not touch the rim during operation.
- Locking handle locks head away from the rim.
- Powerful action bead-breaker blade follows bead to inside rim contour.
- Heavy-duty turntable rotates in either direction.
- Rebuildable stainless steel cylinders.
- Heavy-duty stainless steel turntable.
- Safe, fast, profitable and affordable.
- Pneumatic-locking mount/demount head.
- Sturdy tilt-back tower.
- Tire pressure sensor style rims changes safely.
- Interchangeable locking peaks on jaws.
- Table top rotation double-speed RPM 6-16.
- Shipping weight 573 lbs.
- Also available with air motor.

Same features as the A2024TI

## PLUS SP2000

### SUPER POWER UNIT

+

## PLUS PU1500

### POWER ASSIST UNIT

- Pneumatic powered
- Wheel and bead pressing arm
- Bead lifter
- Maintains bead in drop center
- Eliminates bead stress
- Eliminates wheel damage
- One person operation to change even the most difficult tires
- PAX capable with PAX kit
- Rim clamping assist
- Shipping weight 1080 lbs.

# A2024TI-2015



Same features as the A2024TI

+

## PLUS SP2000 SUPER POWER UNIT

+

## PLUS PNEUMATIC BEAD PRESSING TOOL WITH SUPPORT (BPT)

Professional pneumatic devices for easy demounting and mounting operation of low-profile and Run Flat tires.

- Shipping weight 882 lbs.

# A2024TI-20BPT



## SPECIFICATIONS

• Ext. Rim Size	10"-24"
• Optional w/Adapter	8"-26"
• Int. Rim Size	13"-26"
• Voltage	110V 1 Ph
• Rim Width	2"-15"
• Max. Tire Diameter	43"
• Air Pressure	150 psi
• Bead Breaker Power @ Shoe	3500 lbs
• Torque	737 ft/lbs

## STANDARD ACCESSORIES

- Lube Bucket
- Lube Brush
- Tire Lever
- M/D Head Bottom Inserts
- Set of Jaw Protectors
- B/B Blade Protector
- Bead Clip
- Set of Inserts
- Tire Lever Cover

## LIMITED WARRANTY

- 10 Years on Transmission
- 1 Year on Parts and Labor

